



Lifting Eye Bolt RUD RS-M

Produktinformation

Octagonal lifting eye approved for lifting.

Kennzeichnung: nach Norm, CE-Kennzeichnung

Standard: EN 1677-1

Sicherheitsbeiwert: 4:1

Artikel-Nr.	Code	Tragfähigkeit t	Gewinde	Augendurch. (mm)	A mm	B mm	C mm	D mm	E mm	T mm	Gewicht (kg)	Lieferzeit (in Tagen)
11.4061401	RS-M6	0,1	M6	25	12	11	10	25	25	34	0,1	12
11.4061402	RS-M8	0,2	M8	25	12	11	10	25	25	34	0,1	12
11.4056397	RS-M10	0,25	M10	25	15	11	10	25	25	34	0,1	12
11.4056398	RS-M12	0,4	M12	30	18	13	12	30	30	41	0,18	12
11.4056403	RS-M14	0,75	M14	35	21	15	14	35	35	48	0,29	12
11.4056404	RS-M16	1	M16	35	24	15	14	35	35	48	0,3	12
11.4053850	RS-M18	1,2	M18	40	30	17	16	40	40	55	0,45	12
11.4056407	RS-M20	1,5	M20	40	30	17	16	40	40	55	0,47	12
-	RS-M22	1,5	M22	50	36	21	20	50	50	70	0,87	12
11.4056408	RS-M24	2	M24	50	36	21	20	50	50	70	0,89	12
-	RS-M27	2	M27	60	45	26	24	60	60	85	1,6	12
11.4056409	RS-M30	3	M30	60	45	26	24	60	60	85	1,62	12
-	RS-M33	3	M33	90	50	43	38	90	100	130	6,1	12
11.4056954	RS-M36	4	M36	90	54	43	38	90	100	130	6,5	12
-	RS-M39	5	M39	90	59	43	38	90	100	130	6,5	12
11.4056955	RS-M42	6	M42	90	63	43	38	90	100	130	6,5	12
-	RS-M45	7	M45	90	67	43	38	90	100	130	6,5	12
11.4056956	RS-M48	8	M48	90	67	43	38	90	100	130	6,5	12

Blaupause

