



Lifting Eye RUD VLBG-Z, UNC thread

Produktinformation

- Captive but exchangeable RUD-Bolt
- Bracket adjustable in force direction
- Comprehensive range of threads

Kennzeichnung: nach Norm

Standard: EN 1677-1

Sicherheitsbeiwert: 4:1

| Tragfähigkeit t | Thread Inch | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | I mm | K mm | L mm | N mm | T mm | Gewicht (kg) | Lieferzeit (in Tagen) |
|--------------------|----------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|-----------------|-----------------------|
| 1 | 1/2 -13 | 32 | 54 | 34 | 26 | 38 | 10 | 29 | 22 | 75 | 45 | 50 | 32 | 75 | 0,36 | 12 |
| 1,5 | 5/8 -11 | 33 | 56 | 36 | 30 | 39 | 13,5 | 36 | 24 | 86 | 47 | 60 | 38 | 85 | 0,5 | 12 |
| 2,5 | 3/4 -10 | 50 | 82 | 54 | 45 | 55 | 16,5 | 43 | 28 | 113 | 64 | 71 | 48 | 110 | 1,3 | 12 |
| 4 | 1 -8 | 50 | 82 | 54 | 45 | 67 | 18 | 43 | 41 | 130 | 78 | 84 | 48 | 125 | 1,5 | 12 |
| 8 | 1 1/2 -6 | 77 | 122 | 82 | 70 | 97 | 26,5 | 77 | 62 | 205 | 110 | 140 | 87 | 197 | 6,14 | 12 |

Blaupause

