



Lifting Eye RUD WBG

Produktinformation

The eyes can be loaded with working load limit in all directions. All the eyes are pivoted to avoid breakage in the eyes, which also make it possible to fold it aside when it is not in use. Furthermore, it has a ball-bearing swivel, which makes the lifting eye always stand in the correct direction to the load.

Kennzeichnung: nach Norm, CE-Kennzeichnung

Standard: EN 1677-1

Sicherheitsbeiwert: 4:1.

Artikel-Nr.	Code	Durchmesser mm	Tragfähigkeit t	Gewinde	F Standard	Gewicht (kg)	Lieferzeit (in Tagen)
10990850	WBG-V	36	0,45	M10	17	0,3	12
10990852	WBG-V	42	0,6	M12	21	0,4	12
10990856	WBG-V	48	1,3	M16	25	0,6	12
10990860	WBG-V	64	2	M20	33	1,1	12
10990864	WBG-V	81	3,5	M24	40	2,7	12
10990870	WBG-V	99	5	M30	50	5,5	12
10990900	WBG	90	10	M36	54	4,6	12
10990902	WBG	98	13	M42	63	6,1	12
10990908	WBG	98	13	M48	68	6,3	12
10990912	WBG	120	22	M56	84	10,7	12