



Heavy Duty Air Chain Hoists Red Rooster TMH (37.500 & 45.000 kg)

Produktinformation

The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market.

Standard features:

- Precise variable speed control (cord control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (84 dBA)
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

Recommended:

We highly recommend the use of an SMC air treatment unit. (Sold separately).

Kennzeichnung: nach Norm, CE-Kennzeichnung

Standard: EN 14492-2

Tragfähigkeit t	Typ	Anzahl der Stränge	Luftverbrauch Senken l/sec	Luftverbrauch Heben l/sec	Hubgeschwindigkeit ohne Last (m/min)	Lowering speed with max.load m/min	Hubgeschwindigkeit ohne Last (m/min)	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	Gewicht (kg)	Lieferzeit (in Tagen)
37,5	Cord control	3	180	108	0,9	2	1,8	1.440	1.150	557,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1.300	12
37,5	Pendant control	3	180	108	0,9	2	1,8	1.440	1.150	557,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1.300	12
45	Cord control	3	167	108	0,65	1,8	1,8	1.440	1.150	557,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1.300	12
45	Pendant control	3	167	108	0,65	1,8	1,8	1.440	1.150	557,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1.300	12

Blaupause

