

## Webbing Slings B4

### Produktinformation

Four-layer lifting slings. The width of the sling is increased in relation to the lifting capacity. Ideal for areas where minimum surface pressure is required on the load to be lifted, such as boat lifting. Reinforced folding eyelets as standard.

**Kennzeichnung:** nach Norm, CE-Kennzeichnung

**Standard:** EN 1492-1



Artikel-Nr.	Tragfähigkeit t
41030056F	2
41030055F	2
41030046F	2
41030102F	2
41030103F	2
41030104F	2

41030105F	2
41030106F	2
41030107F	2
41030108F	2
41030109F	4
41030071F	4
41030070F	4
41030067F	4
41030045F	4
41030110F	4
41030111F	4
41030112F	4
41030113F	4
41030114F	4
41030094F	6
41030039F	6
41030054F	6
41030049F	6
41030040F	6
41030115F	6
41030100F	6
41030116F	6
41030117F	6

41030052F	8
41030118F	8
41030119F	8
41030120F	8
41030041F	8
41030091F	8
41030121F	8
41030122F	8
41030089F	8
41030123F	10
41030124F	10
41030097F	10
41030084F	10
41030125F	10
41030095F	10
41030126F	10
41030090F	10
41030151F	16
41030152F	16
41030080F	16
41030051F	16
41030059F	16
41030064F	16

41030048F	16
41030065F	16
41030075F	20
41030098F	20
41030068F	20
41030066F	20
41030127F	20
41030001F	20
41030128F	20
41030053F	20
41030129F	24
41030130F	24
41030131F	24
41030132F	24
41030133F	24
41030134F	24
41030135F	24
41030136F	24