



## Jaw / Jaw Crosby HG-228

### Produktinformation

End fittings are quenched and tempered, bodies heat treated by normalizing.  
Forged jaw ends are fitted with bolts and nuts for 6 mm through 16 mm, and pins and cotters on 19 mm through 70 mm sizes.  
Modified UNJ thread on end fittings for improved fatigue properties.  
Body has UNC threads.

**Standard:** According to Federal Specifications FF-T-791b.

**Sicherheitsbeiwert:** 5:1

Artikel-Nr.	Tragfähigkeit t	Gewinde Durchmesser. & Aufnahme (mm)	Gewindedurchmesser & Aufnahme (inch)	A	B	E	G	J	K	M	N	BB	Gewicht (kg)	Lieferzeit (in Tagen)
				mm	mm	mm	mm	mm	mm	mm	mm	mm		
11.511032518	0,36	7.94 x 114	5/16 x 4-1/2	7,94	12,7	51,2	22	332	218	359	244	116	0,25	12
11.511032536	0,54	9.53 x 152	3/8 x 6	9,53	13,5	53,5	21,5	413	260	445	292	155	0,39	12
11.511032554	1	12.7 x 152	1/2 x 6	12,7	16,3	81,8	27,1	474	321	512	359	153	0,83	12
11.511032572	1	12.7 x 229	1/2 x 9	12,7	16,3	81,3	27,1	633	405	671	443	238	1,04	12
11.511032590	1	12.7 x 305	1/2 x 12	12,7	16,3	81,3	27,1	786	481	824	519	314	1,23	12
11.511032616	1,59	15.9 x 152	5/8 x 6	15,9	20,1	99,1	33,5	501	349	554	402	153	1,46	12
11.511032634	1,59	15.9 x 229	5/8 x 9	15,9	20,1	98,8	33,5	662	434	715	487	239	1,79	12

47070034B	1,59	15.9 x 305	5/8 x 12	15,920,1	98,8	33,5	815	510	868	563	315	2,08	12
11.511032670	2,36	19.1 x 152	3/4 x 6	19,124,6	120	38,5	536	383	601	449	156	2,18	12
11.511032698	2,36	19.1 x 229	3/4 x 9	19,124,6	119	38,5	698	470	764	535	244	2,65	12
47100004B	2,36	19.1 x 305	3/4 x 12	19,124,6	119	38,5	851	546	916	612	320	3,05	12
47070035B	2,36	19.1 x 457	3/4 x 18	19,124,6	120	38,5	1.155	698	1.221	764	471	3,83	12
11.511032750	3,27	22.2 x 305	7/8 x 12	22,229,5	140	44,8	880	575	956	651	309	4,25	12
11.511032778	3,27	22.2 x 457	7/8 x 18	22,229,5	140	44,8	1.197	740	1.272	815	473	5,34	12
11.511032796	4,54	25.4 x 152	1 x 6	25,4 34	155	52,1	605	453	690	538	157	4,74	12
11.511032812	4,54	25.4 x 305	1 x 12	25,4 34	155	52,1	910	605	995	690	309	6,25	12
11.511032830	4,54	25.4 x 457	1 x 18	25,4 34	155	52,1	1.215	757	1.300	843	462	7,77	12
47070033B	4,54	25.4 x 610	1 x 24	25,4 34	154	52,1	1.535	925	1.620	1.010	631	9,51	12
11.511032876	6,89	31.8 x 305	1-1/4 x 12	31,846,7	205	71,5	1.000	695	1.107	802	306	9,94	12
11.511032894	6,89	31.8 x 457	1-1/4 x 18	31,846,7	205	71,5	1.305	848	1.412	955	459	11,7	12
11.511032910	6,89	31.8 x 610	1-1/4 x 24	31,846,7	205	71,5	1.624	1.014	1.731	1.121	625	13,5	12
11.511032938	9,71	38.1 x 305	1-1/2 x 12	38,152,3	227	71,4	1.035	731	1.160	855	313	14,8	12
11.511032956	9,71	38.1 x 457	1-1/2 x 18	38,152,3	227	71,4	1.340	883	1.465	1.008	465	17,2	12
11.511032974	9,71	38.1 x 610	1-1/2 x 24	38,152,3	227	71,4	1.661	1.051	1.786	1.176	633	19,7	12
11.511033018	12,7	44.5 x 457	1-3/4 x 18	44,5 66	238	85	1.355	898	1.503	1.045	467	24,3	12
11.511033036	12,7	44.5 x 610	1-3/4 x 24	44,5 66	238	85	1.660	1.050	1.807	1.198	619	27,7	12
11.511033054	16,8	51.0 x 610	2 x 24	50,866,5	300	95	1.769	1.159	1.949	1.339	622	43,7	12
11.511033072	27,2	63.5 x 610	2-1/2 x 24	63,577,7	337	113	1.853	1.244	2.087	1.478	625	75,9	12
11.511033090	34	70.0 x 610	2-3/4 x 24	69,993,7	379	106	1.899	1.289	2.172	1.562	626	90,1	12

# Blaupause

