



Car Lashing VDI 2700 35mm LC 1500daN Comfort handle Swivel hooks

Produktinformation

An auto transporter belt with a 3-point attachment system that meets VDI 2700 8.1 standards, guaranteeing the safe transport of vehicles. The product provides excellent transmission and uniform distribution of standard tension force (STF). The belt achieves the required performance level of $ETA \geq 0.5$. Minimized belt stretch of 4% ensures reliable load stability, reducing the need for re-tensioning during transport.

The 35mm belt kit includes:

- 35mm 2.8m polyester belt
- 35mm tensioner, LC 1500daN, STF 330daN, dimensions 190x85mm
- 3 swivel hooks
- Grass cover 1.3m

Features:

- Performance ETA coefficient ≥ 0.5
- Label with certificate number and inspector's label on the so-called grass cover
- Meets the requirements of EN 12195-2
- According to VDI 2700 8.1, the belt strap must not come into contact with the tire when securing the vehicle. Therefore, rubber or rubber-material protection must be used!

Kennzeichnung: nach Norm

Standard: VDI 2700, EN 12195-2

Artikel-Nr.	Zurkapazität LC (daN)	Länge m	Bandbreite mm	Beschlagteile	STF daN	Lieferzeit (in Tagen)
25040123F	1.500	2,8	35	Swivel hook	330	12