



## Master link, grade 80

### Produktinformation

Masterlink for chain sling assemblies.

**Kennzeichnung:** nach Norm, CE-Kennzeichnung

**Standard:** EN 1677-4

**Sicherheitsbeiwert:** 4:1

**Güteklasse:** 8

Artikel-Nr.	Tragfähigkeit t	Nutzlänge mm	Für Kette mm, 1-Strang	Für Kette mm, 2-Strang	A mm	B mm	D mm	Gewicht (kg)	Lieferzeit (in Tagen)
42040090F	1,6	110	6/7	6	110	60	13	0,34	2
42040093F	2,12	110	8	7	110	60	16	0,53	2
42040069F	3,15	135	10	8	135	75	18	0,8	2
42040071F	5,3	160	13	10	160	90	22	1,5	2
42040073F	8	180	16	13	180	100	26	2,3	2
42040075F	11,2	200	18	16	200	110	32	3,9	2
42040317F	14	260	20	18	260	140	36	6,35	2
42040078F	17	300	22	20	300	160	40	9	2
42040080F	21,2	340	26	22	340	180	45	12,8	2
42040082F	31,5	350	32	26	350	190	50	17,2	12
42040084F	45	400	36	32	400	200	56	24,2	12

Blaupause

