



## Trägerklemme FSV - FSVS - FSVSU

### Produktinformation

Beam clamp for horizontal lifting and transporting of steel beams and structures. Can also be attached upside down and be used as a (temporary) lifting point. Various models available:

- FSV standard clamp
- FSVS clamp with enlarged jaw opening
- FSVSU clamp with enlarged opening, reinforced body and articulated lifting eye.

#### Features:

- Equal opening and closing of both jaws for simple and quick assembly
- Welded jaw plates for better positioning and less damaging of load
- Lightweight, maintenance-friendly, heavy duty body

**Kennzeichnung:** nach Norm, CE-Kennzeichnung

**Standard:** EN 13155

Artikel-Nr.	Code	Tragfähigkeit t	Flanschbreite mm	S (mm)	T mm	V-max	U-max	H mm	X mm	Gewicht (kg)	Lieferzeit (in Tagen)
44010132B	1 FSV	1	75-190	30	73,5	357	345	113-192	120	5	12
44010051B	2 FSV	2	75-190	30	73,5	357	345	113-192	120	5	12
44010135B	2 FSVS	2	75-420	30	73,5	540	428	114-275	120	7	12
44010133B	3 FSV	3	75-190	30	73,5	357	345	113-192	120	5	12
44010136B	3 FSVS	3	75-420	30	73,5	540	428	114-275	120	7	12
44010139B	3 FSVSU	3	75-420	30	73,5	540	486	114-275	120	8	12
44010108B	4 FSV	4	150-300	40	80	450	422	185-240	180	15	12
44010109B	4 FSVS	4	150-560	40	80	708	545	173-362	180	18	12
44010137B	4 FSVSU	4	150-560	40	80	708	613	173-362	180	21	12
44010131B	5 FSV	5	150-300	40	80	450	422	185-240	180	15	12
44010134B	5 FSVS	5	150-560	40	80	708	545	173-362	180	19,5	12
44010138B	5 FSVSU	5	150-560	40	80	708	622	173-362	180	22	12
44010130B	10 FSV	10	350-450	95	88	695	653	400-447	200	50	12

# Blaupause

