

Roundslings FORANKRA R1 Side Seam

Product information



High-quality roundslings made in accordance with PN-EN 1492-2, a Polish manufacturer who uses only top-grade materials from Europe for their production.

Characteristics:

- Markings: label with abbreviated instructions. Number of black stripes along the sling informs about the lifting capacity in tons.
- The highest versatility of use among slings.
- Excellent ratio of dead weight to lifting load.
- Can be used for lifting materials sensitive to damage, such as bundles of copper pipes, aluminum sections, etc.
- High resistance to moisture and typical contaminants, such as grease and oil.

Material: 100% PES, single sleeve, high quality polyester yarn.

Marking: According to standard, CE-marked

Temperature range: -40°C up to +100°C

Standard: EN 1492-2

Note: Colour Coded

Part Code

**WLL
ton**

41080022F

40

41080023F

40

41080024F

40

41080025F

40

41080026F

40

41080027F	40
41080028F	40
41080029F	40
41080030F	50
41080031F	50
41080032F	50
41080033F	50
41080034F	50
41080035F	50
41080036F	50
41080037F	50
41080038F	60
41080039F	60
41080040F	60
41080041F	60
41080042F	60
41080043F	60
41080044F	60
41080045F	60
41080046F	70
41080047F	70
41080048F	70
41080049F	70

41080050F 70

41080051F 70

41080052F 70

41080053F 70

41080054F 80

41080055F 80

41080056F 80

41080057F 80

41080058F 80

41080059F 80

41080060F 80

41080061F 80