



RUD Lifting Eye Bolt RS-M

Product information

Octagonal lifting eye approved for lifting.

Material: Forged of high strength steel.

Marking: According to standard, CE-marked, WLL, indication for the most unfavourable case

Temperature range: -40°C up to 200°C

Standard: EN 1677-1

Safety factor: 4:1

Part Code	Code	WLL ton	Thread	Eye diam.Ø mm	A mm	B mm	C mm	D mm	E mm	T mm	Weight kg	Delivery time
11.4061401	RS-M6	0.1	M6	25	12	11	10	25	25	34	0.1	12
11.4061402	RS-M8	0.2	M8	25	12	11	10	25	25	34	0.1	12
11.4056397	RS-M10	0.25	M10	25	15	11	10	25	25	34	0.1	12
11.4056398	RS-M12	0.4	M12	30	18	13	12	30	30	41	0.18	12
11.4056403	RS-M14	0.75	M14	35	21	15	14	35	35	48	0.29	12
11.4056404	RS-M16	1	M16	35	24	15	14	35	35	48	0.3	12
11.4053850	RS-M18	1.2	M18	40	30	17	16	40	40	55	0.45	12
11.4056407	RS-M20	1.5	M20	40	30	17	16	40	40	55	0.47	12
-	RS-M22	1.5	M22	50	36	21	20	50	50	70	0.87	12
11.4056408	RS-M24	2	M24	50	36	21	20	50	50	70	0.89	12
-	RS-M27	2	M27	60	45	26	24	60	60	85	1.6	12
11.4056409	RS-M30	3	M30	60	45	26	24	60	60	85	1.62	12
-	RS-M33	3	M33	90	50	43	38	90	100	130	6.1	12
11.4056954	RS-M36	4	M36	90	54	43	38	90	100	130	6.5	12
-	RS-M39	5	M39	90	59	43	38	90	100	130	6.5	12
11.4056955	RS-M42	6	M42	90	63	43	38	90	100	130	6.5	12
-	RS-M45	7	M45	90	67	43	38	90	100	130	6.5	12
11.4056956	RS-M48	8	M48	90	67	43	38	90	100	130	6.5	12

Blueprint

