



Lifting Eye RUD WBG

Product information

The eyes can be loaded with working load limit in all directions. All the eyes are pivoted to avoid breakage in the eyes, which also make it possible to fold it aside when it is not in use. Furthermore, it has a ball-bearing swivel, which makes the lifting eye always stand in the correct direction to the load.

Material: Forged of high strength steel.

Marking: According to standard, CE-marked, WLL

Finish: Striking fluorescent pink powder coating.

Standard: EN 1677-1

Safety factor: 4:1.

| Part Code | Code | Diameter mm | WLL ton | Thread | F Standard | Weight kg | Delivery time |
|-----------|-------|-------------|---------|--------|------------|-----------|---------------|
| 10990850 | WBG-V | 36 | 0.45 | M10 | 17 | 0.3 | 12 |
| 10990852 | WBG-V | 42 | 0.6 | M12 | 21 | 0.4 | 12 |
| 10990856 | WBG-V | 48 | 1.3 | M16 | 25 | 0.6 | 12 |
| 10990860 | WBG-V | 64 | 2 | M20 | 33 | 1.1 | 12 |
| 10990864 | WBG-V | 81 | 3.5 | M24 | 40 | 2.7 | 12 |
| 10990870 | WBG-V | 99 | 5 | M30 | 50 | 5.5 | 12 |
| 10990900 | WBG | 90 | 10 | M36 | 54 | 4.6 | 12 |
| 10990902 | WBG | 98 | 13 | M42 | 63 | 6.1 | 12 |
| 10990908 | WBG | 98 | 13 | M48 | 68 | 6.3 | 12 |
| 10990912 | WBG | 120 | 22 | M56 | 84 | 10.7 | 12 |