



Lifting Eye Starpoint RUD VRM

Product information

Design: Octagonal lifting eye.

For bolts with min. quality class 10.9

Material: Forged of high strength steel.

Marking: According to standard, CE-marked, WLL, indication for the most unfavourable case.

Finish: Striking fluorescent pink powder coating.

Standard: EN 1677-1

Safety factor: 4:1

Part Code	Code	Diameter mm	WLL ton	Thread	WLL straight lift ton	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	K mm	L mm	N mm	T mm	Weight kg	Delivery time
-	VRM	-	0.1	M6	-	9	7	20	23	16	28	17	13	37	11	9	28	0.06	12
11.427992989	VRM	25	0.3	M8	1	11	9	25	25	21	30	21	16.3	47	14	12	35	0.1	12
11.427990311	VRM	25	0.4	M10	1	11	9	25	25	21	30	21	16.3	47	14	12	35	0.1	12
11.427990312	VRM	30	0.75	M12	2	13	10	30	30	24	34	25	19.8	56	17	14	42	0.18	12
11.427990314	VRM	35	1.5	M16	4	15	13	35	36	30	40	29	23.6	65	21	19	49	0.32	12
11.427990315	VRM	40	2.3	M20	6	17	16	40	41	37	50	35	29.3	76	23	24	58	0.48	12
11.427990316	VRM	48	3.2	M24	8	20	19	49	51	45	60	41	35.2	92	29	30	70	0.83	12
46040244B	VRM	60	4.5	M30	12	26	24	60	66	56	75	51	44	114	36	36	87	1.32	12

Blueprint

