



Lifting Eye Starpoint RUD VRS

Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly available, look type VRS-F

Safety factor: 4:1

Part Code	WLL ton	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L mm	M mm	N mm	T mm	Weight kg	Delivery time
42040255B	0.3	11	9	25	25	30	16.3	47	12	M8	6	35	0.11	12
-	0.4	11	9	25	25	30	16.3	47	15	M10	6	35	0.11	12
42040254B	0.75	13	10	30	30	34	19.8	56	18	M12	8	42	0.19	12
-	0.75	13	10	30	30	30	34	19.8	56	18	M14	8	0.2	12
-	1.5	15	13	35	36	40	23.5	65	24	M16	10	49	0.32	12
-	2.3	17	16	40	41	50	29.3	76	30	M20	12	58	0.54	12
-	3.2	20	19	49	51	60	35	92	36	M24	14	70	0.86	12
-	4.5	26	24	60	66	75	44	114	45	M30	17	87	1.5	12
-	7	32	29	73	76	98	53	135	54	M36	22	104	3.3	12

Technical data

Working load limit in metric tons

RUD Load table VRS, VRS-F

Blueprint

