



Lifting Eye VLBG-Z RUD, UNC with variable length

Product information

- Captive but exchangeable RUD-Bolt
- Bracket adjustable in force direction
- Comprehensive range of threads

Temperature range: -40°C up to +100°C

Safety factor: 4:1

WLL ton	Thread Inch	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	K mm	L mm	N mm	T mm	Delivery time
0.63	3/8 -16	30	54	34	24	39	10	29	10-98	75	45	39-127	32	75	12
1	1/2 -13	32	54	34	26	38	10	29	13-123	75	45	42-152	32	75	12
1.5	5/8 -11	33	56	36	30	39	13.5	36	16-148	86	47	52-184	38	85	12
2.5	3/4 -10	50	82	54	45	55	16.5	43	19-185	113	64	62-228	48	110	12
2.5	7/8 -9	50	82	54	45	55	16.5	43	22-211	113	64	65-254	48	110	12
4	1 -8	50	82	54	45	67	18	43	25-211	130	78	68-254	48	125	12
5	1 1/4 -7	60	103	65	60	64	22.5	61	32-278	151	80	93-339	67	147	12
8	1 1/2 -6	77	122	82	70	97	26.5	77	38-270	205	110	115-347	87	197	12
20	2 -4.5	95	156	100	95	105	36	87	51-302	230	130	138-389	100	222	12

Blueprint

