

## Weld-on Lifting Ring RUD VRBK-FIX



### Product information

Load ring for edge attachments. Welded on the corner reduces the number of lifting points. Loadable in any direction. Low profile and 270° pivoting.

**Marking:** According to standard

**Temperature range:** -20° to +200°C.









**Finish:** Pink powder coated.

**Standard:** EN 1677-1

**Safety factor:** 4:1.

Part Code	Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	T mm	Weight kg	Delivery time
11.427902149	VRBK-FIX 4 t	4	32	14	28	48	141	30	65	1	12
11.427902150	VRBK-FIX 6.7 t	6.7	40	20	35	60	181	34	84	2.16	12
11.427902256	VRBK-FIX 10 t	10	52	22	46	65	212	46	94	4.4	12
11.427904653	VRBK-50 t	50	134	70	118	230	626	96	303	76.35	12

## Technical data

Method of lift										
Number of legs	1	1	2	2	2	2	2	3 / 4	3 / 4	3 / 4
Angle of inclination	0°	90°	0 °	90°	0-45°	45-60°	Unsym- metrisch	0-45°	45-60°	Unsym- metrisch
Factor	1	1	2	2	1.4	1	1	2.1	1.5	1
Type	For the max. total load weight >G< in metric tons									
VRBK-FIX 4 t	4	4	8	8	5.6	4	4	8.4	6	4
VRBK-FIX 6.7 t	6.7	6.7	13.4	13.4	9.4	6.7	6.7	14.1	10	6.7
VRBK-FIX 10 t	10	10	20	20	14	10	10	21.2	15	10
VRBK-FIX 16 t	16	16	32	32	22.4	16	16	33.6	24	16
VRBK-FIX 31.5 t	31.5	31.5	63	63	45	31.5	31.5	67	47.5	31.5
VRBK 50 t	50	50	100	100	70	50	50	105	75	50

## Blueprint

