



## Marine C5M Hand Winch MR3000-5000

### Product information

Robust marine winch has a high corrosion resistance due to its many 316 stainless steel parts and 3 layers of C5M offshore coating. The hand winch is IP54 standardised which means that it is resistant to splash water and dust on the inside.

- load pressure brake with double ratchet system for safe stable hold of the load in any position
- closed gearbox to protect against environmental influence - protection classification IP54
- cable outlet upwards, downwards or at rear
- adjustable crank
- suitable for wall and (optional) floor mounting
- brushed steel frame with marine coating DIN/ISO 12944 C5M - RAL9005 (black)
- stainless steel 316 parts: drum, crank and all outgoing shafts, bolts and nuts
- corrosion resistant

#### Options:

- grooved drum (GD)
- 2 drum compartment (2D) or multiple up to 8 (XD)
- suitable for floor mounting (FM)
- suitable for Dyneema rope (DY)
- pressure roller (PR)
- ATEX certified zone 2 and 22 (EX)  
CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C

**Material:** Steel, stainless steel

**Marking:** According to standard, CE-marked

**Finish:** Paint thickness is 240 micron in 3 layers

**Standard:** EN 13157

**Note:** Steel, stainless steel or fiber ropes must be ordered separately

**Safety factor:** 4:1

WLL ton	Model	Rope Ø mm	Rope capacity m	Weight kg	Delivery time
3	MR3000 C5M	14	68.7	104	12
5	MR5000 C5M	18	42.9	135	12

## Blueprint

