

## Low Speed Electric Winch LS5000

### Product information



Low-speed electric winch, made to move fragile loads from 0,3 metres per minute, powerful with its 5 ton lifting capacity in combination with a 230V connection.

- robust and safe electric pulling and lifting winch 400 V / 230 V
- protection classification electric IP55 / mechanical IP54
- mechanical overload protection
- thermal protection electric motor
- low voltage (24 V) pendant switch with 2 m cable
- including 2 m power cable with 16A CEE plug
- automatic grease system for the worm gearing
- 1 layer of paint

#### Options:

- limit switch - required for lifting applications (LS)
- grooved drum (GD)
- 230V - 50Hz

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** - 20°C up to + 40°C

**Finish:** Painted, light grey

**Standard:** EN 14492

**Note:** Steel wire ropes must be ordered separately

| WLL ton | Lifting speed m/min | Motor kW | Capacity top layer kg | Rope diameter mm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | J mm | K mm | L mm | M mm | N mm | P mm | R mm | Weight kg | Delivery time |
|---------|---------------------|----------|-----------------------|------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-----------|---------------|
| 5       | 0,4                 | 0.75     | 3,959                 | 18               | 730  | 704  | 630  | 600  | 169  | 534  | 183  | 322  | 219  | 25   | 351  | 126  | 254  | 427  | 255  | 216       | 12            |

## Blueprint

