



Jaw / Jaw Crosby HG-228

Product information

End fittings are quenched and tempered, bodies heat treated by normalizing.
Forged jaw ends are fitted with bolts and nuts for 6 mm through 16 mm, and pins and cotters on 19 mm through 70 mm sizes.
Modified UNJ thread on end fittings for improved fatigue properties.
Body has UNC threads.

Standard: According to Federal Specifications FF-T-791b.

Material: Steel.

Marking: Logo, size and type.

Finish: Hot dipped galvanized.

Note: Turnbuckles recommended for straight or in-line pull only.

Safety factor: 5:1

Part Code	WLL ton	Thread dia. & take up mm	Thread dia. & take up inch	A mm	B mm	E closed	G mm	J open	K closed	M open	N closed	BB mm	Weight kg	Delivery time
11.511032518	0.36	7.94 x 114	5/16 x 4-1/2	7.94	12.7	51.2	22	332	218	359	244	116	0.25	12
11.511032536	0.54	9.53 x 152	3/8 x 6	9.53	13.5	53.5	21.5	413	260	445	292	155	0.39	12
11.511032554	1	12.7 x 152	1/2 x 6	12.7	16.3	81.8	27.1	474	321	512	359	153	0.83	12
11.511032572	1	12.7 x 229	1/2 x 9	12.7	16.3	81.3	27.1	633	405	671	443	238	1.04	12
11.511032590	1	12.7 x 305	1/2 x 12	12.7	16.3	81.3	27.1	786	481	824	519	314	1.23	12
11.511032616	1.59	15.9 x 152	5/8 x 6	15.9	20.1	99.1	33.5	501	349	554	402	153	1.46	12
11.511032634	1.59	15.9 x 229	5/8 x 9	15.9	20.1	98.8	33.5	662	434	715	487	239	1.79	12

47070034B	1.59	15.9 x 305	5/8 x 12	15.9	20.1	98.8	33.5	815	510	868	563	315	2.08	12
11.511032670	2.36	19.1 x 152	3/4 x 6	19.1	24.6	120	38.5	536	383	601	449	156	2.18	12
11.511032698	2.36	19.1 x 229	3/4 x 9	19.1	24.6	119	38.5	698	470	764	535	244	2.65	12
47100004B	2.36	19.1 x 305	3/4 x 12	19.1	24.6	119	38.5	851	546	916	612	320	3.05	12
47070035B	2.36	19.1 x 457	3/4 x 18	19.1	24.6	120	38.5	1,155	698	1,221	764	471	3.83	12
11.511032750	3.27	22.2 x 305	7/8 x 12	22.2	29.5	140	44.8	880	575	956	651	309	4.25	12
11.511032778	3.27	22.2 x 457	7/8 x 18	22.2	29.5	140	44.8	1,197	740	1,272	815	473	5.34	12
11.511032796	4.54	25.4 x 152	1 x 6	25.4	34	155	52.1	605	453	690	538	157	4.74	12
11.511032812	4.54	25.4 x 305	1 x 12	25.4	34	155	52.1	910	605	995	690	309	6.25	12
11.511032830	4.54	25.4 x 457	1 x 18	25.4	34	155	52.1	1,215	757	1,300	843	462	7.77	12
47070033B	4.54	25.4 x 610	1 x 24	25.4	34	154	52.1	1,535	925	1,620	1,010	631	9.51	12
11.511032876	6.89	31.8 x 305	1-1/4 x 12	31.8	46.7	205	71.5	1,000	695	1,107	802	306	9.94	12
11.511032894	6.89	31.8 x 457	1-1/4 x 18	31.8	46.7	205	71.5	1,305	848	1,412	955	459	11.7	12
11.511032910	6.89	31.8 x 610	1-1/4 x 24	31.8	46.7	205	71.5	1,624	1,014	1,731	1,121	625	13.5	12
11.511032938	9.71	38.1 x 305	1-1/2 x 12	38.1	52.3	227	71.4	1,035	731	1,160	855	313	14.8	12
11.511032956	9.71	38.1 x 457	1-1/2 x 18	38.1	52.3	227	71.4	1,340	883	1,465	1,008	465	17.2	12
11.511032974	9.71	38.1 x 610	1-1/2 x 24	38.1	52.3	227	71.4	1,661	1,051	1,786	1,176	633	19.7	12
11.511033018	12.7	44.5 x 457	1-3/4 x 18	44.5	66	238	85	1,355	898	1,503	1,045	467	24.3	12
11.511033036	12.7	44.5 x 610	1-3/4 x 24	44.5	66	238	85	1,660	1,050	1,807	1,198	619	27.7	12
11.511033054	16.8	51.0 x 610	2 x 24	50.8	66.5	300	95	1,769	1,159	1,949	1,339	622	43.7	12
11.511033072	27.2	63.5 x 610	2-1/2 x 24	63.5	77.7	337	113	1,853	1,244	2,087	1,478	625	75.9	12
11.511033090	34	70.0 x 610	2-3/4 x 24	69.9	93.7	379	106	1,899	1,289	2,172	1,562	626	90.1	12

Blueprint

