



## Lifting Arm NEO HV

## **Product information**

## NEO HV LIFTING ARM WITH PERMANENT MAGNET

The Neo HV lifting arm, in connection with a Neo lifting magnet, is a versatile aid for handling loads from the horizontal to the vertical position and vice versa. For example, if a plate is on a pallet and you need to move it to a lathe, you must usually make use chains, clamps, and at least two workers. With a lifting arm equipped with a Neo permanent lifting magnet, you will save manpower and make the operation more efficient.

The Neo HV is a lifting arm, thanks to which, in combination with a lifting magnet, you can easily turn a workpiece from the horizontal to the vertical position. You will appreciate this when handling sheets, metal plates and round materials for lathes and horizontal machining centres.

Advantages:

- Possibility to adjust the arm to a wide range of diameters and widths
- Removable lifting arm for magnet replacement
- Robust lifting eye

Marking: According to standard

Temperature range: Material -10°C up to +70°C, environment 0°C up to +50°C. Beware of leaving the clamp in direct sunlight. Finish: Painted.

Standard: EN 13155

Note: Only suitable for NEOLIFT and NEO HOT, which have to be ordered separately.

Safety factor: 3:1

| Part Code | Code     | WLL<br>ton | Width<br>mm | W<br>mm | L<br>mm | H<br>mm | Weight<br>kg | Delivery time |
|-----------|----------|------------|-------------|---------|---------|---------|--------------|---------------|
| 44030045B | LARM250  | 0.25       | 300-800     | 210     | 958     | 244     | 26           | 12            |
| 44030046B | LARM500  | 0.5        | 300-1,000   | 210     | 1,158   | 244     | 41           | 12            |
| 44030047B | LARM1000 | 1          | 300-1,000   | 210     | 1,211   | 297     | 73           | 12            |

## Blueprint

