



## Endless webbing slings FORANKRA 0,5 - 10 t

### Product information

Single-layered endless webbing slings are also available with a double layer, which doubles the workload capacity for the same sling width.

Color coded.

**Material:** Polyester

**Temperature range:** -40°C up to 100°C

**Note:** Standard dimensional tolerance is  $\pm 3\%$ . Lengths can vary within the tolerance range!.

**Part Code**

**WLL  
ton**

41040041F

1

41040044F

1

41040047F

1

41040212F

1

41040053F

1

41040055F

1

41040056F	1
41040057F	1
41040058F	1
41040065F	2
41040069F	2
41040071F	2
41040073F	2
41040074F	2
41040075F	2
41040076F	2
41040078F	2
41040079F	2
41040080F	2
41040081F	2
41040085F	3
41040086F	3
41040087F	3
41040088F	3
41040089F	3
41040090F	3
41040091F	3
41040092F	3
41040093F	3

41040094F	3
41040095F	4
41040097F	4
41040174F	4
41040100F	4
41040188F	4
41040189F	4
41040103F	4
41040190F	4
41040104F	5
41040191F	5
41040106F	5
41040107F	5
41040108F	5
41040192F	5
41040176F	5
41040193F	5
41040194F	6
41040195F	6
41040179F	6
41040196F	6
41040111F	6
41040197F	6

41040198F	6
41040199F	8
41040200F	8
41040201F	8
41040202F	8
41040203F	8
41040204F	8
41040205F	8
41040180F	10
41040181F	10
41040035F	10
41040183F	10
41040184F	10