



Chain Block POWERTEX Blackline PCB-S2

Product information







Chain Block POWERTEX Blackline PCB-S2 is a hoist of high quality which is durable and easy to operate using the ergonomic hand chain. The hoist is powder coated in matt black, and mounted with a black chain, which makes it perfect for use on stages and in the amusement industry.

The hoist is in a compact, lightweight construction.

Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Sprocket wheel equipped with needle bearings and drive shaft supported by needle bearing and slide bearing inside to ensure smooth and efficient operation
- Safe, well covered automatic load reaction brake
- Equipped with 2 brake pawls and 4 brake springs (double safety compared to EN 13157 requirement)
- Fine calibrated European made COROLIM® protected load chain for smooth operation
- The unique surface treatment gives excellent corrosion protection and quiet run
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- · Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each hoist
- Spare parts available

Option:

Chain bag

Material: Durable all steel construction

Marking: According to standard, CE-marked, UKCA-marked, POWERTEX, Model, WLL, Chain, Serial number, User manual/OR code

Temperature range: -10°C up to +50°C

Finish: Powder coated body in matt black and plated frame components

Standard: EN 13157, EN 818-7

Safety factor: 4:1

Part Code	WLL ton	Lifting height m	Model	Load chain mm	Hand chain mm	Number of falls	Hand force max. kg	A mm ı		C mm	D mm	H min mm	Weight kg	Delivery time
16.10PCBS20050030BK	0.5	3	PCB-S2BK/500KG	5,0 x 15,0	5,0 x 23,7	1	21.5	130	128	22	34	280	8.9	12
16.10PCBS20050060BK	0.5	6	PCB-S2BK/500KG	5,0 x 15,0	5,0 x 23,7	1	21.5	130	128	22	34	280	9.8	12
16.10PCBS20050080BK	0.5	8	PCB-S2BK/500KG	5,0 x 15,0	5,0 x 23,7	1	21.5	130	128	22	34	280	17.95	12
16.10PCB0050100BK	0.5	10	PCB-S2BK/500KG	5,0 x 15,0	5,0 x 23,7	1	21.5	130	128	22	34	280	19	12
16.10PCBS20050090BK	0.5	9	PCB-S2BK/500KG	5,0 x 15,0	5,0 x 23,7	1	21.5	130	128	22	34	280	19.4	12
16.10PCBS20100030BK	1	3	PCB-S2BK/1000KG	6,3 x 19,0	5,0 x 23,7	1	29.1	150	145	26	39	330	11.7	12
16.10PCBS20100060BK	1	6	PCB-S2BK/1000KG	6,3 x 19,0	5,0 x 23,7	1	29.1	150	145	26	39	330	12	12
16.10PCBS20100100BK	1	10	PCB-S2BK/1000KG	6,3 x 19,0	5,0 x 23,7	1	29.1	150	145	26	39	330	21.4	12

Blueprint

