



Bow Shackle POWERTEX PBSP Blackline

Product information

POWERTEX



Bow type shackle PBSP is a high quality shackle intended for use in demanding environments.

It is supplied with screw pin for quick and easy opening/closing.

Blackline is suitable for use in the entertainment industry and in theatres where the dark surface gives little visual reflection.

The shackle comply to EN 13889, AS 2741 and meets the performance requirements of US Federal Specification RR-C-271 Type IVA Class 2, Grade A.

Features:

- Safe – All POWERTEX shackles are manufactured and tested in accordance to EN 13889
- All bodies and bolts marked with batch number for traceability
- The bow is forged in closed dies
- All parts are made from alloy steel being quenched and tempered
- Blackline products are painted to give little visual reflection
- Multilanguage user manuals

Material: Forged alloy steel, supplied with alloy screw pin.

Marking: According to standard, POWERTEX (PT or PTEX) , WLL, CE, size, grade and batch number.

Temperature range: -40°C up to +200°C

Finish: Up to 3/8", matt black powder painted 1/2" and up, matt black electro galvanized

Standard: EN 13889

Safety factor: 6:1.

Part Code	Code	WLL	Nominal size In.	a* mm	c* mm	d mm	d1 mm	d2 mm	e mm	H1 mm	Weight	Delivery time
11.31PBSP00050BK	1332	0.5	1/4	13	29	6.5	8	17.5	20	38	0.048	12
11.31PBSP00075BK	1333	0.75	5/16	13.5	31	8	9.5	21	21.5	42.5	0.082	12
11.31PBSP00100BK	1334	1	3/8	17	36.5	10	11.2	25	26.2	51.5	0.15	12
11.31PBSP00200BK	1336	2	1/2	20.6	47.75	12.7	15.8	30.5	33.3	67	0.3	12
11.31PBSP00325BK	1337	3.25	5/8	27	60	16	19	40	43	85	0.65	12
11.31PBSP00475BK	1338	4.75	3/4	32	71.5	19	22	48	51	98.5	1.01	12

Blueprint

