



## Car Lashing VDI 2700 35mm 1500daN Standard handle

### Product information



An auto transporter belt with a 3-point attachment system that meets VDI 2700 8.1 standards, guaranteeing the safe transport of vehicles. The product provides excellent transmission and uniform distribution of standard tension force (STF). The belt achieves the required performance level of  $ETA \geq 0.5$ . Minimized belt stretch of 4% ensures reliable load stability, reducing the need for re-tensioning during transport.

The 35mm belt kit includes:

- 35mm polyester belt 2.8m
- 35mm tensioner, LC 1500daN, STF 330daN, dimensions 190x85mm
- 3 swivel hooks
- Grass type cover 1,3m

Features:

- Performance ETA coefficient  $\geq 0.5$
- Label with certificate number and inspector's label on the so-called grass cover
- According to VDI 2700 8.1, the belt strap must not come into contact with the tire when securing the vehicle. Therefore, rubber or rubber-material protection must be used!

**Material:** Polyester

**Marking:** According to standard

**Standard:** EN 12195-2

**Note:** Stretchability  $\leq 4\%$

| <b>Part Code</b> | <b>LC<br/>daN</b> | <b>Length<br/>m</b> | <b>Band width<br/>mm</b> | <b>Design</b> | <b>Fitting</b> | <b>Delivery time</b> |
|------------------|-------------------|---------------------|--------------------------|---------------|----------------|----------------------|
|------------------|-------------------|---------------------|--------------------------|---------------|----------------|----------------------|

|           |       |     |    |        |             |    |
|-----------|-------|-----|----|--------|-------------|----|
| 25040126F | 1,500 | 2.8 | 35 | 2-part | Swivel hook | 12 |
|-----------|-------|-----|----|--------|-------------|----|