

Lashing system ERGO 50mm STF 500 daN LC 2500daN



Product information



Lashing system LC 2500 daN Ergo has an ergonomically designed tensioner where the longer handle has reversed tension to create a natural movement, which also results in 30% higher tensioning force compared to conventional lashings. By using Ergo the number of top-over lashings (friction lashings) can be reduced when securing the goods. Ergo is a price worthy lashing commonly used by transport companies and suitable for all kinds of cargo carriers. Ergo lashings has a higher lashing capacity (LC) than regular Standard lashing. All components are tested and of very high quality to ensure a long durability and high safety. The strap is made of a high strength polyester webbing, which makes the lashing very flexible and durable. - Standard Tension Force (STF) for Ergo is 500 daN at SHF 50 Hand Force.

Material: Poliester & Steel

Marking: According to standard

Standard: EN 12195-2

Note: Label in lashing system ERGO is sewn into webbing to secure it. Standard length of short part is 0,5m.

| Part Code | LC daN | 2xLC (daN) | Length m | Width | Design | Fitting | STF daN | Packing/pallet units | Packing Qty. | Weight kg | Delivery time |
|-----------|--------|------------|----------|-------|--------|------------------|---------|----------------------|--------------|-----------|---------------|
| 25010232F | 2,500 | 5,000 | 4 | 50 | 2-part | Wire hook double | 500 | - | - | 1.7 | 12 |
| 25010243F | 2,500 | 5,000 | 6 | 50 | 2-part | Wire hook double | 500 | 192 | 8 | 2.21 | 2 |
| 25010266F | 2,500 | 5,000 | 8 | 50 | 2-part | Wire hook double | 500 | 144 | 6 | 2.98 | 2 |
| 25010290F | 2,500 | 5,000 | 10 | 50 | 2-part | Wire hook double | 500 | 144 | 6 | 3.24 | 2 |
| 25010298F | 2,500 | 5,000 | 12 | 50 | 2-part | Wire hook double | 500 | 144 | 6 | 3.75 | 12 |