



Single webbing slings 1 - 5 t

Product information

Single layer lifting slings. The width of the sling is high with respect to the workload. Perfect for places, where minimal surface pressure on the load to be lifted is needed, for example when lifting boats. Folded reinforced eyes as standard and also available with flat eyes.

Thanks to our own production unit, we can also make quick deliveries of special types and lengths as well as lifting slings with higher WLL.

Features: RFID-ready

Material: 100% polyester

Marking: CE-marked

Temperature range: -40°C - +100 °C

Note: Color coded

Warning: Standard dimensional tolerance is $\pm 3\%$. Lengths can vary within the tolerance range!

Safety factor: 7:1

Part code

WLL ton

41010076F

1

41010077F

1

41010074F

1

41010078F

1

41010043F

1

41010072F

1

41010063F	1
41010079F	1
41010080F	1
41010081F	1
41010082F	2
41010045F	2
41010073F	2
41010044F	2
41010083F	2
41010084F	2
41010085F	2
41010086F	2
41010087F	2
41010088F	2
41010089F	3
41010039F	3
41010046F	3
41010047F	3
41010090F	3
41010071F	3
41010091F	3
41010092F	3
41010093F	3

41010094F	4
41010095F	4
41010034F	4
41010096F	4
41010033F	4
41010097F	4
41010098F	4
41010099F	4
41010100F	4
41010050F	5
41010101F	5
41010102F	5
41010048F	5
41010103F	5
41010060F	5
41010104F	5
41010105F	5