



Geared trolley SIVA HKS

Product information

Geared trolley for IPE and T beams. The trolley moves on the beam by pulling the hand chain. The wheels are equipped with duration lubricated ball bearings. The width of the trolley can be adjusted by a threaded rod (10 and 20 t models with washers, in the picture). The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -10°C - (+)50°C

Finish: Painted, yellow

Standard: EN 13157

Safety factor: 4:1

[User manual in English, Swedish, Finnish, Polish, Czech and Hungarian.](#)

| Part Code | WLL ton | Beam width mm | Min. Radius Curve m | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | Weight kg | Delivery time |
|------------|---------|---------------|---------------------|-------|------|-------|------|------|------|------|------|-----------|---------------|
| 43030016F | 1 | 58-220 | 0.7 | 353.5 | 238 | 183 | 17 | 31 | -3 | 68 | 95 | 12.5 | 12 |
| 43030017F | 2 | 66-220 | 0.9 | 362 | 277 | 208 | 20 | 31 | -3 | 80 | 108 | 17 | 12 |
| 43030018F | 3 | 74-220 | 1.2 | 406.5 | 324 | 249 | 26 | 31 | -3 | 100 | 131 | 28 | 2 |
| 43030019F | 5 | 90-220 | 1 | 434.5 | 373 | 296.5 | 28 | 40 | -5 | 120 | 154 | 45 | 2 |
| 43030013F | 10 | 125-203 | 1.3 | 487.5 | 455 | 490 | 82 | 36.5 | -5 | - | - | 93 | 2 |
| SIVA200HKS | 20 | 136-203 | 4.7 | 523 | 642 | 622 | 110 | 54 | -5 | - | - | 247.5 | 12 |

Blueprint

