

Magnetic lifting clamps MAGPML

Product information



Durable magnet clamps for lifting plates, pipes and round steel bars. Small and easy to use. Due to the joint lifting eye, improved durability and stability of the item to be lifted. Rubber coated handle is comfortable to use.

Safety factors

- 100 - 300 kg clamps: 3.5:1
- 600 - 2,000 kg clamps: 3:1

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+) 80 °C

Finish: Painted, yellow

Standard: EN 13155

Note: Handles also available as a spare part

Warning: Not to be heat-treated

[User manual in English, Swedish, Finnish, Polish, Czech and Hungarian.](#)

Part code	WLL ton	WLL round materials t	B mm	H mm	L mm	R mm	Weight kg	Delivery time
44030002F	0.1	0.04	62	67	92	126	3	2
44030003F	0.3	0.125	92	88	158	150	10	2
44030004F	0.6	0.25	122	113	228	186	24	2
44030005F	1	0.4	176	158	258	282	37	2
44030006F	2	0.75	234	206	378	374	85	12

Technical data

MIN. PLATE AND BAR MATERIAL THICKNESSES

Product code	Min. plate thickness mm	Min. bar diameter mm
MAGPML100	30	55
MAGPML300	40	70
MAGPML600	50	80
MAGPML1000	60	90
MAGPML2000	70	100

SPARE PARTS

Spare part (product code)	Description	Suitable for clamp (product code)
MAG100KAUV	Operating hand lever	MAGPML100
MAG300KAUV	Operating hand lever	MAGPML300
MAG600KAUV	Operating hand lever	MAGPML600
MAG1000KAUV	Operating hand lever	MAGPML1000
MAG2000KAUV	Operating hand lever	MAGPML2000
MAGPML100NS	Lifting shackle Incl. bolt and fasteners	MAGPML100
MAGPML300NS	Lifting shackle Incl. bolt and fasteners	MAGPML300
MAGPML600NS	Lifting shackle Incl. bolt and fasteners	MAGPML600
MAGPML1000NS	Lifting shackle Incl. bolt and fasteners	MAGPML1000

MAGPML2000NS

Lifting shackle | Incl. bolt and
fasteners

MAGPML2000

Also other spare parts available with a delivery time, ask our sales for more information

Blueprint

