



Lifting eye screw with swivel NS8KL, grade 80

Product information

Lifting screw with swivel for all lifting directions. Also available with longer 120 mm thread.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C - (+)200°C

Finish: Painted, yellow

Standard: EN 1677-1

Safety factor: 4:1

Part Code	WLL ton	Thread mm	Thread length mm	diameter eye inside mm	Ø of eye mm	Thread pitch mm	b mm	g mm	t mm	Weight kg	Delivery time
46030006F	0.45	M10	18	55x30	14	1,5	36	51	41	0.43	2
46030007F	0.5	M12	18	55x30	14	1,75	36	51	41	0.44	2
46030008F	1.1	M16	20	55x30	14	2	36	52	42	0.46	2
46030009F	1.1	M16	120	55x30	14	2	36	52	42	0.46	2
46030010F	2	M20	30	70x34	16	2,5	50	68	56	0.96	2
46030019F	2	M20	120	70x34	16	2,5	50	68	56	0.96	12
46030020F	3.2	M24	120	85x37	18	3	57	78	65.5	1.45	2
46030012F	3.2	M24	40	85x37	18	3	57	78	65.5	1.45	2
46030023F	5.3	M30	120	85x37	20	3,5	66	97	80.5	2.17	2
46030013F	5.3	M30	35	85x37	20	3,5	66	97	80.5	2.17	12
46030014F	8	M30	35	115x50	22	3,5	80	112	92	3.57	2
46030024F	8	M30	120	115x50	22	3,5	80	112	92	3.57	2
46030015F	8	M36	50	115x50	22	4	80	109	89.5	4.17	2
46030026F	8	M36	120	115x50	22	4	80	109	89.5	4.17	2
46030027F	10	M42	50	115x50	25	4,5	80	109	89.5	3.67	2
46030016F	10	M48	50	115x50	25	5	80	109	89.5	4.02	12
46030028F	10	M45	60	115x50	25	4,5	80	109	89.5	4.17	2
46030017F	15	M56	84	152x70	32	5,5	117	310	280	11.6	2

Technical data

WORKING LOAD LIMITS

Thread	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	Tight. torque
					0 - 45°	45-60°	0 - 45°	45-60°	Nm
M10	0,9	0,45	1,8	0,9	0,63	0,45	0,95	0,68	10-16
M12	1	0,5							

Blueprint

