

Stainless steel lifting eye nut DIN 582



Product information

Stainless steel lifting eye for vertical lifting.

Material: AISI 316

Marking: According to standard, CE-marked

Temperature range: -40°C - (+)200°C

Finish: Polished

Standard: DIN 582

Note: Only for vertical lifting

Warning: Not to be heat-treated

Safety factor: 4:1

Part Code	WLL ton	Thread mm	b mm	c mm	d mm	e mm	f mm	Weight kg	Delivery time
NSMH06L	0.08	M6	20	36	20	8.5	36	0.05	12
NSMH08L	0.14	M8	20	36	20	8.5	36	0.05	12
NSMH10L	0.23	M10	25	45	25	10	45	0.09	12
NSMH12L	0.34	M12	30	54	30	11	53	0.16	12
NSMH16L	0.7	M16	35	63	35	13	62	0.24	12
NSMH20L	1.2	M20	39	71	39	14	70	0.36	12

Technical data

WORKING LOAD LIMITS

	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Thread	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)
					0 - 45°	45-60°	0 - 45°	45-60°
M6	0,08		0,16		-		-	
M8	0,14		0,28		0,1		0,14	
M10	0,23		0,46					

Blueprint

