

Stainless steel Lifting eye screw NSRHL DIN 580



Product information

Stainless steel lifting eye for vertical lifting.

Material: AISI 316

Marking: According to standard, CE-marked

Temperature range: -40°C - (+)200°C

Finish: Polished

Standard: DIN 580

Note: Only for vertical lifting

Warning: Not to be heat-treated

Safety factor: 4:1

Part Code	WLL ton	Thread mm	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg	Delivery time
NSRH06L	0.08	M6	20	36	20	13	6	36	0.06	12
48020011F	0.14	M8	20	36	20	13	6	36	0.06	12
48020006F	0.23	M10	25	45	25	17	8	45	0.11	12
48020002F	0.34	M12	30	54	30	20.5	10	53	0.18	12
48020003F	0.7	M16	35	63	35	27	12	62	0.28	12
48020004F	1.2	M20	39	71	39	30	14	70	0.45	12

Technical data

WORKIN LOAD LIMITS

	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Thread	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)
					0 - 45°	45-60°	0 - 45°	45-60°
M6	0,08		0,16		-		-	
M8	0,14		0,28		0,1		0,14	
M10	0,23		0,46					

Blueprint

