

## Stainless steel Lifting eye screw NSRHL DIN 580



### Product information

Stainless steel lifting eye for vertical lifting.

**Material:** AISI 316

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C - (+)200°C

**Finish:** Polished

**Standard:** DIN 580

**Note:** Only for vertical lifting

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

Part Code	WLL ton	Thread mm	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg	Delivery time
NSRH06L	0.08	M6	20	36	20	13	6	36	0.06	12
48020011F	0.14	M8	20	36	20	13	6	36	0.06	12
48020006F	0.23	M10	25	45	25	17	8	45	0.11	12
48020002F	0.34	M12	30	54	30	20.5	10	53	0.18	12
48020003F	0.7	M16	35	63	35	27	12	62	0.28	12
48020004F	1.2	M20	39	71	39	30	14	70	0.45	12

## Technical data

### WORKIN LOAD LIMITS

	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Thread	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)
					0 - 45°	45-60°	0 - 45°	45-60°
M6	0,08		0,16		-		-	
M8	0,14		0,28		0,1		0,14	
M10	0,23		0,46					

# Blueprint

