

## Weld-on lifting point NS8HI, grade 80



### Product information

Weld-on lifting point for all lifting directions. Equipped with a spring that holds the eye in desired position.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C - (+)200°C

**Finish:** Painted, yellow

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 8

Part Code	WLL ton	A mm	B mm	D mm	M mm	Weight kg	Delivery time
46040006F	1.12	41	78.5	13	37	0.4	12
46040007F	2	42	88	14	40	0.47	2
46040008F	3.15	45	94	17	42.5	0.69	2
46040009F	5.3	55	118	22	50	1.46	2
46040010F	8	70	141	26.5	66.5	2.5	12
46040029F	15	97	188	34	90	5.79	2

## Technical data

### WORKING LOAD LIMITS

Product	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)
					0 - 45°	45-60°	0 - 45°	45-60°
NS8HI1	1,12	1,12	2,24	2,24	1,57	1,12	2,35	1,68
NS8HI2	2	2	4	4	2,8	2	4,2	3
NS8HI3	3,15							

## Blueprint

