



Shackles, SAE - bow model SAK PBP

Product information

Shackles approved for lifting. Bow shackles are suitable for use when more than one attachment is to be made to the body (multi-leg systems), or to allow freedom of movement in the plane of the bow. Screw pin shackles are easily manipulated. They are typically suitable for non-permanent applications and one-off installations, when there is no tendency for the pin to unscrew and the shackle can be observed under operation.

Features: RFID-ready

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -20°C - (+)200°C

Finish: Hot dip galvanized

Standard: US. FED. SPEC. RR-C-271F

Safety factor: 6:1

Part Code	WLL ton	Size inch	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	M mm	N mm	Weight kg	Delivery time
46010032F	0.33	3/16	10	7	22	5	15	14	25	38	4	29	5	0.03	2
46010033F	0.5	1/4	12	8	29	7	20	16	33	47	5	35	5	0.05	2
46010036F	0.75	5/16	14	10	31	8	22	19	38	53	6	42	8	0.09	2
46010040F	1	3/8	17	11	37	10	26	23	45	63	7	52	10	0.14	2
46010052F	1.5	7/16	19	13	43	11	30	27	52	74	8	61	11	0.17	2
46010061F	2	1/2	21	16	48	13	34	30	59	84	10	69	13	0.33	2
46010070F	3.25	5/8	27	19	61	16	43	38	75	106	11	85	18	0.62	2
46010077F	4.75	3/4	32	23	72	19	51	46	89	126	13	101	21	1.07	2
46010082F	6.5	7/8	37	26	84	23	58	53	102	148	13	114	25	1.64	2
46010088F	8.5	1	43	29	96	26	69	61	119	167	14	129	27	2.28	2
46010091F	9.5	1-1/8	46	32	108	30	74	69	131	190	16	142	32	3.36	2
46010046F	12	1-1/4	52	35	119	33	93	76	146	210	18	156	35	4.31	2
46010049F	13.5	1-3/8	57	38	133	36	92	84	162	233	19	174	38	6.14	12
46010172F	17	1-1/2	61	42	146	39	99	92	175	254	21	187	41	7.8	12
46010066F	25	1-3/4	73	51	178	47	127	106	225	313	26	231	57	12.6	12
42040140F	35	2	83	57	197	53	146	122	253	348	31	263	61	20.4	12
46010190F	55	2-1/2	105	70	267	69	184	145	327	453	35	330	80	38.9	12
46010086F	85	3	127	82	330	76	200	165	367	546	38	490	105	70	12

Blueprint

