

Shackles, SAE - bow model with locking SAK PLBP



Product information

Shackles approved for lifting. Bow shackles are suitable for use when more than one attachment is to be made to the body (multi-leg systems), or to allow freedom of movement in the plane of the bow. Locking bolt shackles are recommended for long-term and permanent installations, or when there is a natural tendency for the pin to unscrew (rotate) in the application, or when the shackle cannot be observed under operation.

Features: RFID-ready

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -20°C - (+)200°C

Finish: Hot dip galvanized

Standard: US. FED. SPEC. RR-C-271F

Safety factor: 6:1

Part Code	WLL ton	Nominal size In.	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	N mm	Weight kg	Delivery time
46010034F	0.5	1/4	12	8	29	7	20	16	33	47	7	0.05	12
46010037F	0.75	5/16	14	10	31	8	22	19	38	53	8	0.1	12
46010041F	1	3/8	17	11	37	10	26	23	45	63	10	0.15	2
46010054F	1.5	7/16	19	13	43	11	30	27	52	74	11	0.22	2
46010063F	2	1/2	21	16	48	13	34	30	59	84	13	0.36	2
46010071F	3.25	5/8	27	19	61	16	43	38	75	106	18	0.76	2
46010078F	4.75	3/4	32	23	72	19	51	46	89	126	21	1.23	2
46010083F	6.5	7/8	37	26	84	23	58	53	102	148	25	1.79	2
46010089F	8.5	1	43	29	96	26	69	61	119	167	27	2.57	2
46010092F	9.5	1-1/8	46	32	108	29	74	69	131	190	32	3.75	2
46010047F	12	1-1/4	52	35	119	32	83	76	146	210	35	5.31	2
46010194F	13.5	1-3/8	57	38	133	35	92	84	162	233	38	7.18	2
46010059F	17	1-1/2	61	42	146	38	99	92	175	254	41	9.43	2
46010067F	25	1-3/4	73	51	178	45	127	106	225	313	57	15.4	12
46010074F	35	2	83	57	197	51	146	122	256	348	61	23.7	12
46010171F	55	2-1/2	105	70	267	67	184	145	327	453	80	44.61	12
46010100F	85	3	127	83	330	76	200	165	365	546	92	70	12
46010186F	120	3-1/2	133	96	372	92	229	203	419	626	105	120	12

Blueprint

