

## Anchorage Point 8-281 PSA-YEP



### Product information



- Rotates through 360° adjustable in the direction of the load.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Passed 150 kg dynamic fall testing ( EU standard is 100 kg).
- Meets all requirements of the German BG BAU ( Employer's insurance association of the building industry).
- Correspond to the European Directive for "personnel protection equipment" (89/686/EWG).
- PSA - Lifting point to be as an anchor point for personal protective equipment.

**Features:** Built-in RFID/NFC chip

**Material:** Manufactured from forged alloy steel, quenched and tempered

**Marking:** According to standard, number of persons, standards, individual serial number, manufacturer, production year, product ID

**Finish:** Yellow Painted

**Standard:** EN 795, EN 365, EN 50308

Part Code	Max. number of persons	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	S mm	W mm	M mm	Weight kg	Delivery time
46010151B	1	10	45	30	10	11	18	33	29	5	45	8	52	M12 x 1.75	0.2	12
46010152B	2	30	52	35	14	13	24	35	33	8	52	10	61	M16 x 2	0.3	12
46010153B	2	70	60	40	16	15	30	44	37	7	60	12	70	M20 x 2.5	0.6	12

# Blueprint

