



## **Eye Point Stainless Steel 8-S291**

## **Product information**

• Rotates through 360° adjustable in the direction of the load.

• Individual forged parts and cap screw are traceable to Test Certification.

• Bolts are Metric thread.

• Proof tested to 2.5 times the WLL.

• Fatigue rated to 20,000 cycles at 1.5 times the WLL.

• Quick and simple assembly, just a tapped hole is required.

• Used in different applications such as chemical oil coal industries, food processing,

Material: Stainless Steel

Marking: According to standard, CE-marked

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Part Code	WLL ton	Torque Nm	Thread M mm	Thread length (E) mm	Pitch DIN13	A mm	B mm	C mm	D mm	F mm	G mm	H mm	J mm	S mm	W mm	Weight kg	Delivery time
11.428-S291-005	0.5	10	M12	18	1.75	45	30	10	11	33	29	5	44	8	52	0.2	12
11.428-S291-010	1	30	M16	24	2	52	35	14	13	35	33	5	51	10	61	0.3	12
11.428-S291-020	2	70	M20	30	2.5	60	40	16	15	44	37	7	60	12	70	0.6	12
11.428-S291-025	2.5	150	M24	36	3	72	49	19	18	52	46	10	72	14	84	1	12

## Blueprint

