



## Clevis sling hook with latch SALKH, grade 80

### Product information

Clevis sling hook with latch, grade 80.

Hook is equipped with spring loaded safety latch. Attachment directly to the chain with clevis link.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-2

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

Part Code	WLL ton	EWL mm	For chain dia. mm	K mm	H mm	E mm	M mm	R mm	B mm	Weight kg	Delivery time
42040164F	1.12	76	6	76	23	26	8	35	32	0.32	2
42040167F	2	85	7/8	85	32	29	9.5	37	37	0.48	2
42040156F	3.15	104	10	104	35	32	13	46	49	0.95	2
42040158F	5.3	128	13	128	42	36	16	56	56	1.8	2
42040160F	8	150	16	150	54	55	21	60	70	3.4	2
42040162F	12.5	180	20	180	58	61	24	79	77	6	2

## Technical data

### SPARE PARTS

Spare part set (product code)   Inc. latch, spring and pin/nut	Fits the hook (product code)
SALKHVO6S	SALKH6
SALKHVO78S	SALKH78
SALKHVO10S	SALKH10
SALKHVO13S	SALKH13
SALKHVO16S	SALKH16
SALKHVO20S	SALKH20

# Blueprint

