

Excavator hook KAKO, weldable, grade 80



Product information

Weld-on excavator hook for excavator dippers, work machines and vehicles.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-1

Safety factor: 4:1

Grade: 8

| Part Code | WLL ton | A mm | W mm | P mm | T mm | L mm | H mm | F mm | Weight kg | Delivery time |
|-----------|---------|------|------|------|------|------|------|------|-----------|---------------|
| 42040009F | 2 | 5 | 80 | 25 | 20 | 94 | 24 | 34 | 0.8 | 12 |
| 42040010F | 3 | 6 | 115 | 30 | 24 | 105 | 30 | 36 | 1.2 | 2 |
| 42040011F | 5 | 10 | 155 | 34 | 28 | 132 | 43 | 44 | 2.5 | 2 |
| 42040012F | 8 | 12 | 160 | 34 | 38 | 135 | 51 | 51 | 3.3 | 2 |
| 42040013F | 10 | 15 | 200 | 50 | 39 | 167 | 55 | 53 | 5.2 | 2 |
| 42040345F | 15 | 14 | 241 | 54 | 45 | 184 | 67 | 61 | 7.9 | 12 |

Technical data

SPARE PARTS

| Spare part set (product code) Inc. latch, spring and pins | Fits the hooks (product code/s) |
|---|---------------------------------|
| KAKOKOR02 | KAKO02, KAKO03 |
| KAKOKOR05 | KAKO05, KAKO08 |
| KAKOKOR10 | KAKO10 |

Blueprint

