



Eye grab hook LYKA, grade 100

Product information

Eye grab hook is used for shortening chain legs of a sling. The grab hook is attached to the master link with the same connection link as the chain.

Material: Steel

Marking: CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, blue

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

| Part Code | WLL ton | For chain dia. mm | P mm | K mm | A mm | Weight kg | Delivery time |
|-----------|---------|-------------------|------|------|------|-----------|---------------|
| 42050044F | 1.4 | 6 | 8 | 71 | 14 | 0.2 | 2 |
| 42050045F | 2.5 | 8 | 10 | 91 | 18 | 0.28 | 2 |
| 42050046F | 4 | 10 | 13 | 127 | 22 | 0.72 | 2 |
| 42050048F | 6.7 | 13 | 16 | 163 | 28 | 1.6 | 2 |
| 42050050F | 10 | 16 | 19 | 183 | 36 | 2.45 | 2 |
| 42050053F | 16 | 20 | 24 | 227 | 43 | 4.72 | 2 |
| 42050054F | 19 | 22 | 27 | 260 | 48 | 8.2 | 2 |

Blueprint

