



Eye self-locking hook with ball bearing swivel VAKLKL, grade 80

Product information

The hook locks automatically when lifting starts and rotates easily also with full load.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-3

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Part Code	WLL ton	EWL mm	For chain dia. mm	A mm	B mm	C mm	L1 mm	L mm	T mm	E mm	M mm	N mm	Ø mm	Weight kg	Delivery time
42040342F	1.12	160	6	32	11	34	160	194	28	32	70	15	34	0.71	12
42040322F	2	202	7/8	36	13	40	202	240	35	39	88	20	44	1.1	12
42040338F	3.15	283	10	42	16	48	237	283	45	48	108	26	58	2	12
42040340F	5.3	282	13	50	17	58	282	343	52	65	134	33	70	4	12
42040343F	8	342	16	61	22	60	342	419	63	65	169	38	86	7.3	12
42040339F	12.5	483	20	76	27	75	400	483	86	85	186	50	97	11.6	12
42040341F	15	564	22	97	33	97	466	564	76	80	202	52	98	16	12

Blueprint

