



Eye sling hook with latch SALK, grade 80

Product information

Hook is equipped with spring loaded safety latch.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-2

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Part Code	WLL ton	EWL mm	For chain dia. mm	K mm	E mm	F mm	R mm	A mm	Weight kg	Delivery time
42040152F	1.12	76	6	108	24	9	21	20	0.3	2
42040155F	2	90	7/8	133	30	11	26	25	0.4	2
42040142F	3.15	117	10	167	34	15	39	38	0.9	2
42040144F	5.3	152	13	213	39	19	54	43	1.7	2
42040146F	8	178	16	255	46	23	64	50	3.2	2
42040148F	12.5	226	20	305	40	24	80	62	5.8	2
42040149F	15	249	22	348	71	32	80	62	8.5	2
42040150F	21.2	284	26	394	81	35	82	64	13	2
42040151F	31.5	346	32	480	102	37	112	68	17	2

Technical data

SPARE PARTS**Spare part set (product code) | Inc. latch, spring and pin/nut****Fits the hook (product code)**

SALKVO6S

SALK6

SALKVO78S

SALK78

SALKVO10S

SALK10

SALKVO13S

SALK13

SALKVO16S

SALK16

SALKVO20S

SALK20

SALKVO22S

SALK22

SALKVO26S

SALK26

SALKVO32S

SALK32

Blueprint

