



Foundry eye hook VAL, grade 80

Product information

Foundry eye hook with a wide mouth opening are attached to the chain with connecting slings.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-1

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Part Code	WLL ton	EWL mm	For chain dia. mm	P mm	H mm	K mm	D mm	A mm	M mm	Weight kg	Delivery time
46060014F	1.12	124	6	62	29	163	17	39	26	1	2
46060016F	2	122	7/8	63	31	163	18	39	25	1.09	12
46060004F	3.15	150	10	76	38	200	22	50	32	2.04	2
46060006F	5.3	180	13	89	44	238	27	63	38	3.22	2
46060008F	8	210	16	102	52	278	32	76	46	5.53	2
46060010F	12.5	240	20	114	65	325	38	89	55	8.75	2
46060011F	15	272	22	127	69	361	45	102	57	11.93	2
46060012F	21.2	302	26	140	77	402	67	126	66	16.8	12
46060013F	31.5	340	32	153	97	461	81	151	80	26.6	12

Blueprint

