



## Latch hook with ball bearing swivel SALKLKL, grade 80

### Product information

Hook is equipped with spring loaded safety latch. Due to the swivel the hook is easy to align into the wanted direction.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-2

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

| Part Code | WLL ton | EWL mm | For chain dia. mm | A mm | B mm | E mm | M mm | L1 mm | L mm | N mm | C mm | H mm | Weight kg | Delivery time |
|-----------|---------|--------|-------------------|------|------|------|------|-------|------|------|------|------|-----------|---------------|
| 42040327F | 1.12    | -      | 6                 | 33   | 33   | 24   | 69   | 138   | 168  | 16   | 11   | 19   | 0.65      | 12            |
| 42040202F | 2       | 170    | 8                 | 45   | 36   | 28   | 88   | 170   | 208  | 20   | 13   | 23   | 0.95      | 2             |
| 42040193F | 3.15    | 207    | 10                | 53   | 42   | 31   | 105  | 207   | 254  | 23   | 15   | 29   | 1.71      | 2             |
| 42040195F | 5.3     | 248    | 13                | 64   | 50   | 40   | 135  | 248   | 305  | 32   | 17   | 38   | 3.13      | 2             |
| 42040197F | 8       | 295    | 16                | 68   | 61   | 45   | 161  | 295   | 367  | 37   | 21   | 45   | 5.44      | 2             |
| 42040326F | 12.5    | 356    | 20                | 90   | 74   | 56   | 194  | 356   | 434  | 49   | 25   | 50   | 9.5       | 12            |

## Blueprint

