



Latch hook with ball bearing swivel SALKLKL, grade 80

Product information

Hook is equipped with spring loaded safety latch. Due to the swivel the hook is easy to align into the wanted direction.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-2

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

| Part Code | WLL ton | EWL mm | For chain dia. mm | A mm | B mm | E mm | M mm | L1 mm | L mm | N mm | C mm | H mm | Weight kg | Delivery time |
|-----------|---------|--------|-------------------|------|------|------|------|-------|------|------|------|------|-----------|---------------|
| 42040327F | 1.12 | - | 6 | 33 | 33 | 24 | 69 | 138 | 168 | 16 | 11 | 19 | 0.65 | 12 |
| 42040202F | 2 | 170 | 8 | 45 | 36 | 28 | 88 | 170 | 208 | 20 | 13 | 23 | 0.95 | 2 |
| 42040193F | 3.15 | 207 | 10 | 53 | 42 | 31 | 105 | 207 | 254 | 23 | 15 | 29 | 1.71 | 2 |
| 42040195F | 5.3 | 248 | 13 | 64 | 50 | 40 | 135 | 248 | 305 | 32 | 17 | 38 | 3.13 | 2 |
| 42040197F | 8 | 295 | 16 | 68 | 61 | 45 | 161 | 295 | 367 | 37 | 21 | 45 | 5.44 | 2 |
| 42040326F | 12.5 | 356 | 20 | 90 | 74 | 56 | 194 | 356 | 434 | 49 | 25 | 50 | 9.5 | 12 |

Blueprint

