



Master link oversized NORV, grade 80

Product information

Extra large masterlink for chain sling assemblies.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Part Code	WLL ton	EWL mm	For chain mm, 1-leg	For chain mm, 2-leg	A mm	B mm	D mm	Weight kg	Delivery time
42040299F	3.2	190	10	7/8	190	100	16	0.86	12
42040101F	6.4	300	13	10	300	210	25	5.53	2
42040079F	7	210	13	10	210	110	22	1.83	2
42040102F	11	300	16	13	300	210	32	5.94	12
42040081F	11.5	270	16	13/16	270	140	28	3.8	12
42040083F	17	270	22	20	270	140	32	5.05	12
42040330F	19	400	22	20	420	220	38	10.78	12
42040085F	25.1	420	26	22	270	140	38	7.29	12
42040087F	27	470	26	22	470	250	45	17.06	2
42040088F	45	380	36	32	380	200	50	17.65	12
42040331F	65	430	36	32	430	220	60	28.85	12

Blueprint

