



Master link NOR, grade 80

Product information

Masterlink for chain sling assemblies.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Part Code	WLL ton	EWL mm	For chain mm, 1-leg	For chain mm, 2-leg	A mm	B mm	D mm	Weight kg	Delivery time
42040090F	1.6	110	6/7	6	110	60	13	0.34	2
42040093F	2.12	110	8	7	110	60	16	0.53	2
42040069F	3.15	135	10	8	135	75	18	0.8	2
42040071F	5.3	160	13	10	160	90	22	1.5	2
42040073F	8	180	16	13	180	100	26	2.3	2
42040075F	11.2	200	18	16	200	110	32	3.9	2
42040317F	14	260	20	18	260	140	36	6.35	2
42040078F	17	300	22	20	300	160	40	9	2
42040080F	21.2	340	26	22	340	180	45	12.8	2
42040082F	31.5	350	32	26	350	190	50	17.2	12
42040084F	45	400	36	32	400	200	56	24.2	12

Blueprint

