



Manual Chain Hoist KITO CB ATEX

Product information

General: This chain hoist gives you safe operation in potentially explosive atmosphere. It is protected against explosive gases, vapors and dust. Hereby KITO ensures the qualified use of the KITO CB ATEX chain hoist series conforming to the ATEX Directive. Available for use in T4 temperature environments.

Options:

- Different suspension types include: include top hook and KITO Universal Trolleys TS model ATEX version (plain or hand geared trolley configurations) for improved load control.
- Overload Protection Device (OLL): the unique slip clutch mechanism protects the hoist from damage in the event of an excessive overload without increasing the size of the unit.
- Special capacities are available on request.

Marking: Type plate with WLL, CE-marking and serial number.

Finish: Painted.

Safety factor: 4:1

Part code	WLL ton	Lifting height m	Number of falls	Type	Load chain mm	Hand force max. kg	a mm	b mm	d mm	e mm	f mm	g mm	s mm	c mm	Weight kg	Delivery time
43050155B	0.5	2.5	1	CB005 ATEX	6.3 x 19	29	162	161	2,500	71	99	39	42.5	295	11.5	12
43050156B	1	2.5	1	CB010 ATEX	7.1 x 21	35	171	182	2,500	78	112	34	47.5	350	14.5	12
43050157B	2	3	2	CB020 ATEX	7.1 x 21	33	171	235	3,100	78	162	42.5	56	510	24	12
43050158B	3	3	2	CB030 ATEX	9.0 x 27	34	192	282	3,600	91	194	46.5	63	600	41	12

Blueprint

