



Chain Block KITO M3

Product information

General: KITO M3 Series Chain Hoists are built with premium grade components for long life in demanding industrial and contracting applications. M3 lever hoists feature double-reduction gearing for reduced size and weight. Safe, reliable mechanical brake activates instantly, holds the load securely. Double reduction gearing for a smaller hoist that requires minimum power to operate. Spring loaded free-wheel for fast, easy load chain free-wheeling. Open load sheave allows easy inspection and cleaning without dismantling the unit. Maintenance free sealed gears and brake protected against damage from dust and water.

Material: High impact steel housing, chain grade 10.

Marking: CE-marked, WLL, code.

Temperature range: -40°C up to +60°C

Finish: Painted.

Safety factor: 5:1

Part Code	Code	WLL ton	Lifting height m	Bridgeheight mm	Hook width mm	Load chain Ø mm	Number of falls	a mm	b mm	d mm	e mm	f mm	g mm	s mm	t mm	u mm	v mm	w mm	x mm	Weight kg	Delivery time
16.10CB005SSH025	CB005	0.5	2.5	24	27,0	5	1	158	161	2,500	69	99	27	35.5	12.1	17	77	35	89	10	12
16.10CB010SSH025	CB010	1	2.5	29	29,0	6,3	1	162	161	2,500	71	99	29	42.5	16	21.8	93	41	101	11.5	12
16.10CB015SSH025	CB015	1.5	2.5	35	34,0	7,1	1	171	182	2,500	78	112	34	47.5	19.5	26.5	106	47	119	14.5	12
16.10CB020SSH030	CB020	2	3	36	36,0	8	1	185	202	3,000	87	125	36	50	21.8	30	116	49	124	20	12
16.10CB030SSH030	CB030	3	3	36	42,5	7,1	2	171	235	3,100	78	162	42.5	56	27.2	37.5	138	57	148	24	12
16.10CB050SSH030	CB050	5	3	34	46,2	9	2	192	282	3,600	91	194	46.5	63	34.5	47.5	161	67.5	172	41	12
16.10CB075SSH035	CB075	7.5	3	35	72,5	9	3	192	373	4,200	91	253	72.5	85	47.5	63	231	97.5	275	63	12
16.10CB100SSH035	CB100	10	3.5	36	72,5	9	4	192	438	4,200	111	308	72.5	85	47.5	63	231	97.5	295	83	12

Blueprint

