



Electric Chain Hoist KITO ER2 Single Speed Series

Product information

Electric chain hoist with hook suspension

General: The KITO ER2 Electric Chain Hoists are durable, safe and easy to use hoists. It has a top hook or overhead mounting suspension, aluminium die-cast body, electromagnetic brake and a canvas chain container. It lifts from 125 kg up to 5 tons.

Standard configuration:

- 400 V/50 Hz
- Contactor control for single speed
- CH-Meter: operating hours /number of starts
- Ergonomic push button control
- Upper-lower limit switch
- Nickel-plated load chain class grade 80 (DAT) in accordance with Norm EN 818-7
- Thermal protector
- Carbon friction clutch

Options:

- 500 V/Contactor control
- 230 V/50 Hz/60 Hz, 3 phase
- Rubber bumpers for motorized trolleys
- Additional mechanical brake
- Electrical overload limiter
- Acoustic overload signal
- Radio remote control
- Variable speed control
- Level limit switch
- Steel chain container
- Trolley versions: motorized, geared and plain

Note: Can also be delivered with infinitely variable speed control, programmable level limits and cylinder control.

Part Code	Code	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Lifting motor Output (kW)	Lifting motor Rating (%ED)	Lifting speed* 50Hz m/min	Class ISO/FEM	Additional weight per 1 m lift	Test load kg	Load chain mm	Weight kg	Delivery time
43010028B	ER2-001H	0.125	3	14,1	1	0,56	60	14,1	M5/2m	0.42	156	4,3 x 12	27	12
43010051B	ER2-003S	0.25	3	9,1	1	0,56	60	9,1	M5/2m	0.42	313	4,3 x 12	27	12
43010052B	ER2-003H	0.25	3	13,4	1	0,56	60	13,4	M5/2m	0.81	313	6,0 x 16,8	37	12
43010071B	ER2-005L	0.5	3	3,8	1	0,9	60	3,8	M5/2m	0.81	625	6,0 x 16,8	33	12
43010070B	ER2-005S	0.5	3	7,3	1	0,56	60	7,3	M5/2m	0.81	625	6,0 x 16,8	37	12
43010099B	ER2-010L	1	3	3,5	1	0,9	60	3,5	M5/2m	1.33	1,250	7,7 x 21,5	47	12
43010098B	ER2-010S	1	3	7,1	1	0,9	60	7,1	M5/2m	1.33	1,250	7,7 x 21,5	54	12
43010084B	ER2-016S	1.6	3	4,5	1	1,8	60	4,5	M5/2m	2.3	2,000	10,2 x 28,5	72	12
43010122B	ER2-020L	2	3	3,7	1	1,8	60	3,7	M4/1Am	2.3	2,500	10,2 x 28,5	73	12
43010121B	ER2-020S	2	3	7	1	3,5	60	7,0	M4/1Am	2.3	3,130	10,2 x 28,5	91	12
43010112B	ER2-025S	2.5	3	5,7	1	3,5	60	5,7	M4/1Am	2.8	4,000	11,2 x 31,3	104	12
43010135B	ER2-032S	3.2	3	4,4	2	3,5	60	4,4	M4/1Am	4.7	6,250	10,2 x 28,5	107	12
43010142B	ER2-050S	5	3	2,9	2	3,5	60	2,9	M4/1Am	5.6	-	11,2 x 31,3	132	12

Technical data

Dimensions

WLL	Produkt	Min. headroom C	D	a	b	d	e	f	g	h	i
tons	code	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
0,125	ER2-001H	350	430	478	321	219	259	260	27	99	93
0,250	ER2-003S	350	430	478	321	219	259	260	27	99	93
0,250	ER2-003H	370	490	510	348	242	268	283	27	113	106
0,500	ER2-005L	370	490	513	348	242	271	283	27	113	106
0,500	ER2-005S	370	490	510	348	242	268	283	27	113	106
1	ER2-010L	430	550	589	376	291	298	335	31	129	118
1	ER2-010S	430	550	598	376	291	307	335	31	129	118
1,6	ER2-016S	510	630	646	427	308	338	384,5	34	160,5	137,5
2	ER2-020L	575	630	646	427	308	338	384,5	39	160,5	137,5
2	ER2-020S	590	630	703	427	347	356	384,5	39	160,5	137,5
2,5	ER2-025S	625	840	736	445	337	399	437,5	39	173,5	142,5
3,2	ER2-032S	785	920	703	427	347	356	397	44	216	82
5	ER2-050S	850	920	736	445	337	399	439	47	231,5	84,5

Blueprint

